

OWAcolor | OWAlifetime collection
Mineral ceilings in 20 selected colours



OWAcolor





















INSPIRING.
CREATIVE.
INDIVIDUAL.

OWAcolor | OWAlifetime collection

Mineral ceilings in 20 selected colours

INSPIRING.
CREATIVE.
INDIVIDUEL.

Discover the possibilities of inspiring colour worlds with our OWAcolor colour concept for mineral ceilings. With this selection, we offer you the opportunity to incorporate our OWA ceilings into your creative interior design. Let your creativity run free and use OWA to create individualised rooms in which you feel comfortable and enjoy spending time.

 Cole stone blue similar to NCS S 7010-R70B	 Nature apricot similar to NCS S 0530-Y80R	 Sea green similar to NCS S 6020-B90G	 Blue anthracite similar to NCS S 7005-B20G
 Fog green similar to NCS S 2005-G	 Ant red similar to NCS S 4040-Y70R	 Williams pear yellow similar to NCS S 2040-Y	 Marzipan white similar to NCS S 0804-Y50R
 Fox red similar to NCS S 2070-Y80R	 Off white similar to NCS S 1005-Y60R	 Crimson red similar to NCS S 5040-Y90R	 Ginger grey similar to NCS S 3005-Y50R
 Horizon blue similar to NCS S 4030-R90B	 Sand brown similar to NCS S 3020-G80Y	 Terracotta brown similar to NCS S 3040-Y60R	 Clay grey similar to NCS S 3502-Y20R
 Mineral wool grey similar to NCS S 2002-R	 Frost blue similar to NCS S 3010-B30G	 Tulle violet similar to NCS S 3010-R70B	 Smoky grey similar to NCS S 7000-N

Product information

Material:	Mineral tile, fleece covered
Reaction to fire:	A2-s1,d0 (EN 13501-1) (non-flammable)
Thickness:	14 mm
Colours ² :	20 OWAcolor concept-colours
Sound absorption ¹ :	$\alpha_w = 0,85$ and NRC = 0,85
Sound insulation ¹ :	$D_{n,f,w} =$ up to 22 dB and CAC up to 23 dB
Humidity resistance:	up to 95% RH, short-term
Resistance to fire (EN) ¹ :	up to REI 45 (EN 13501-2)
Dimensions:	600 x 600 mm (1200 x 600 mm) 625 x 625 mm (1250 x 625 mm)
Available Edge:	3
Seal of quality:	Leed Credit-capable



¹depending on the system, the ceiling and other additional measures

²Due to the natural material, colour deviations are possible (samples available)



Please scan the QR code for further product information.

Odenwald Faserplattenwerk GmbH
Dr.-F.-A.-Freundt-Straße 3
63916 Amorbach | Germany

info@owa.de
www.owa.de